

Crown Bevcan, Europe &amp; Middle East

www.crowncork.com

 Status: **Approved**

 Issue Date: **19 January 2018**

 Version Number: **1**

 Authorised By: **Florent Gourven**

Nominal Fill Volume :	<b>237ml</b>
Container Brimful Capacity :	<b>265ml +/- 1.8</b>
Individual Axial Load :	<b>800N min.</b>
Minimum Dome Reversal Pressure :	<b>6.2bar</b>
Internal Lacquer Specification :	<b>Water Based Epoxy</b>
External Base Protection :	<b>Single Rim Coat</b>
Nominal Bright Container Weight :	<b>9.3g</b>



## Can Specification

Entity Code	Entity Description	Value	Tolerance
B	Inside Neck Diameter	52.40 mm	±.30
D	Outside Can Diameter	66.30 mm	max.
E	Flange Width	2.10 mm	±.25
Et	Flange Thickness	.169 mm	nom.
F	Flange Diameter	57.26 mm	max.
H	Open Can Height	88.05 mm	±.30
HS	Freeboard Depth	12.20 mm	nom.
J	Neck Seaming Clearance	3.00 mm	min.
kd	Stand Diameter	46.63 mm	
N	Neck Length	17.40 mm	
rb	Flange Radius	1.52 mm	nom.
XB	Flange Angle	<b>7.5° max</b>	

